Pre-Contractual Data Information: Connected Product (EU Data Act)

Product	7526A-256
Firmware / HW	Various (firmware field-updatable via the rear-panel service port; HW: multi-function DC voltage, DC current, resistance/RTD and thermocouple source-measure electronics, optional pressure module interface)
Connectivity / Interfaces	RS-232 serial (DB9) and IEEE-488 (GPIB)
Contact	privacypolicy@fluke.com

1) Product data

- **Physical measurements:** Values sourced or measured on the primary and isolated inputs/outputs: DC voltage, DC current, resistance/RTD, thermocouple, and (with optional pressure modules) pressure
- **Device identifiers:** Model number and firmware version (readable via remote command; firmware is field-updatable via the rear-panel service port); serial number on the rear label
- **Status / telemetry:** Current function/range selected, measured/sourced value, LCD contrast/backlight settings, and remote-interface selection (RS-232 or GPIB) status
- **Events & diagnostics:** Status register conditions (checked via the remote interface's status-check commands)
- **Configuration values:** Function/range setpoints, GPIB address, remote-interface baud/parameters, and calibration constants
- **Other:** None accessible beyond the configuration values above

Estimated volume (typical): <1 KB per RS-232/IEEE-488 command/response; no continuous or background logging

Collection Frequency: On-event only (front-panel actions and RS-232/IEEE-488 remote commands)

For general operational guidance, please refer to the product's user manual.

2) Data formats

Users read live values on the front-panel LCD and can query/set measurements and settings over the RS-232 serial or IEEE-488 (GPIB) interface, including with Fluke's MET/CAL calibration software; there is no on-device file export.

- **On export:** ASCII text command/response strings over RS-232/IEEE-488 (no CSV/JSON/XML file export from the instrument itself). Full remote command set documented in the 7526A Users Manual, LCD and Remote Interface Setup Procedures chapter.
- **On device/in transit:** ASCII serial/GPIB strings terminated with CR/LF; no on-device file storage, no removable media, and no network interface.

3) Storage & retention

- **On-device storage:** Yes. Non-volatile memory retains configuration (function/range setpoints, GPIB address, remote-interface selection) and calibration constants; there is no time-series measurement logging on the instrument.
- **Cloud / servers:** No. The instrument itself has no network or cloud connectivity; no data is transmitted to Fluke servers.
- **Retention:** Configuration and calibration constants retained indefinitely until changed; live measurements are not stored on the instrument (transmitted on demand only).
- **Deletion/anonymization:** Calibration constants can be reset/recalibrated by the user; no personal data is collected, so no anonymization applies.

4) User access, export & erase

- **Where:** Front-panel LCD display and keypad (local), and the RS-232 serial or IEEE-488 (GPIB) remote command interface.
- **How:** Read/set values on the display, or connect a PC/GPIB controller (via the included USB-to-serial adapter or a GPIB cable) and issue remote commands to retrieve measurements and settings.
- **Export formats:** ASCII text strings via RS-232 or IEEE-488.
- **Limits/rate-limits:** Throughput limited by the RS-232 baud rate (9600) or GPIB bus speed; no removable-media or network export.
- **Request erasure:** Reset configuration/calibration constants via the front-panel menus; no personal data is stored on the instrument to erase.

5) Data Sharing with Third Parties

To the extent Fluke has access to the relevant data, you may authorize a third party to access such data by contacting Fluke using the details set out above, specifying the recipient and purpose of the data sharing. You may view and revoke authorized data transfers at any time via the same contact details.

Where data is stored locally on your device or within your own environment and is not accessible to Fluke, you are responsible for granting third-party access directly.

6) Terms of service, contract term & termination

As provided in the quote, order form, or agreement between you and Fluke. If you purchased the product through a distributor or reseller, the terms of service, contract term and termination are as agreed between you and that seller.

7) How Data Holder uses the data

If Fluke has access to any data generated through your use of a Fluke connected product or related service, this will be used in accordance with the applicable agreement between you and Fluke, through which you purchase Fluke’s products or services. The relevant Fluke entity details will be specified in the quote or order form as applicable.

Fluke may engage third parties to act as service providers and perform certain tasks on its behalf, such as processing or storing data generated in connection with your use of a Fluke connected product or related service. For more information, please visit **https://www.fluke.com/en-us/fluke/privacy-policy**

8) Trade secrets

No trade secrets are contained in the data.

9) Right to lodge a complaint

If you have a complaint relating to your Fluke connected product or related service, or the Data Act in general, you can contact Fluke using the details set out above. You also have the right to lodge a complaint with the relevant competent authority designated under Article 37 of the EU Data Act, in the Member State of your habitual residence, place of work or establishment.

Notice version: 1.0 **Last updated:** 2026-08-26