Pre-Contractual Data Information: Connected Product (EU Data Act)

Product	7252 SERIES
Firmware / HW	Various (firmware v1R66, readable via *IDN?; HW: dual-range pressure controller with two integrated pressure controllers)
Connectivity / Interfaces	RS-232 serial and IEEE-488 (GPIB); SCPI command set
Contact	privacypolicy@fluke.com

1) Product data

- **Physical measurements:** Measured and controlled pressure from two integrated pressure controllers / two full-scale ranges; the RUSKA 7252 combines two ranges and two controllers in one instrument
- **Device identifiers:** Model number, serial number, and firmware version (via the *IDN? SCPI query and on the display; firmware v1R66)
- **Status / telemetry:** Current setpoint, measured pressure, active range/controller, control mode/status, and limit status
- **Events & diagnostics:** System error queue and status registers queried over the remote interface (SCPI status model)
- **Configuration values:** Setpoint, range/controller selection, low/high/slew limits, pressure units, communication parameters (RS-232, GPIB address), and calibration parameters
- **Other:** None accessible beyond the configuration values above

Estimated volume (typical): <1 KB per RS-232/IEEE-488 SCPI command/response; no continuous or background logging

Collection frequency: On-event only (front-panel actions and RS-232/IEEE-488 queries)

For general operational guidance, please refer to the product’s user manual.

2) Data formats

Users read live values on the front-panel display and can query/set measurements and settings remotely over RS-232 or IEEE-488 (GPIB) using SCPI; there is no on-device file export.

- **On export:** ASCII text responses to SCPI commands over RS-232/IEEE-488 (CSV/JSON/XML file export is responsibility of customer application). Full command set documented in the RUSKA 7252 users guide.
- **On device/in transit (if relevant):** ASCII serial/GPIB strings; no on-device file storage, no removable media, and no network interface.

3) Storage & retention

- **On-device storage:** Yes. Non-volatile memory retains configuration (setpoints, range selection, limits, units, communication parameters) and calibration parameters; no time-series measurement logging.
- **Cloud / servers:** No. No network or cloud connectivity; no data is transmitted to Fluke servers.

- **Retention:** Configuration and calibration parameters retained indefinitely until changed; live measurements are not stored (transmitted on demand only).
- **Deletion/anonymization:** Configuration/calibration can be reset by the user; no personal data is collected, so no anonymization applies.

4) User access, export & erase

- **Where:** Front-panel display and keypad (local), and the RS-232 serial or IEEE-488 (GPIB) remote command interface.
- **How:** Read values on the display, or connect a PC/controller and issue SCPI query commands to retrieve measurements and settings.
- **Export formats:** ASCII text strings via RS-232 or IEEE-488.
- **Limits/rate-limits (if any):** Throughput limited by the RS-232 baud rate or GPIB bus speed; no removable-media or network export.
- **Request erasure:** Reset configuration/calibration via the front-panel menus; no personal data is stored to erase.

5) Data Sharing with Third Parties

To the extent Fluke has access to the relevant data, you may authorize a third party to access such data by contacting Fluke using the details set out above, specifying the recipient and purpose of the data sharing. You may view and revoke authorized data transfers at any time via the same contact details.

Where data is stored locally on your device or within your own environment and is not accessible to Fluke, you are responsible for granting third-party access directly.

6) Terms of service, contract term & termination

As provided in the quote, order form, or agreement between you and Fluke. If you purchased the product through a distributor or reseller, the terms of service, contract term and termination are as agreed between you and that seller.

7) How Data Holder uses the data

If Fluke has access to any data generated through your use of a Fluke connected product or related service, this will be used in accordance with the applicable agreement between you and Fluke, through which you purchase Fluke's products or services. The relevant Fluke entity details will be specified in the quote or order form as applicable.

Fluke may engage third parties to act as service providers and perform certain tasks on its behalf, such as processing or storing data generated in connection with your use of a Fluke connected product or related service. For more information, please visit **https://www.fluke.com/en-us/fluke/privacy-policy**

8) Trade secrets

No trade secrets are contained in the data.

9) Right to lodge a complaint

If you have a complaint relating to your Fluke connected product or related service, or the Data Act in general, you can contact Fluke using the details set out above. You also have the right to

lodge a complaint with the relevant competent authority designated under Article 37 of the EU Data Act, in the Member State of your habitual residence, place of work or establishment.

Notice version: 1.0 **Last updated:** 2026-08-26