Pre-Contractual Data Information: Connected Product (EU Data Act)

Product	Ti480U, Ti401U, Ti300U Product Family
Firmware / HW	Various
Connectivity / Interfaces	SD card
Contact	privacypolicy@fluke.com

1) Product data

- Physical measurements
  - Thermal images: temperatures reported for each pixel of a sensing array. For example, 640x480, 320x240, etc. These measurements are captured in “radiometry image files” – with file extension .JPG and .IS5 for single-frame images and movies, respectively.
- Device identifiers
  - Model code is one of Ti480U, Ti401U, Ti300U.
  - Serial number follows the form ZSSSSSSSSS, where SSSSSSSSS is the index of the production unit (no further subdivision is available).
- Status / telemetry – No telemetry is provided for device operation/usage.
- Events & diagnostics – No telemetry is provided of warnings, alarms or error codes.
- Configuration values – Certain image-specific settings (image marker locations, emissivity coefficients, etc.) are retained in camera memory and are “factory-resettable” via on-device menus. These settings are recorded within JPG and IS5 files for later use by customer and Fluke software.
- Other – Audio recordings, typed-in text notes and ancillary visible light image captures are also recorded within the JPG and IS5 files and made available for later use by customer and Fluke software.

Estimated volume (typical): typically 1 megabyte per JPG file and 33 megabytes per second of recording for IS5.

Collection frequency: where the “Time-Lapse” feature is available on the camera at all (available by model spec), the collection frequency for JPG files is configurable by the user between 1 per ~2 seconds and hourly or multi-hour intervals. Where Time-Lapse is not available, collection frequency is determined by the user’s manually controlled capture rate.

For general operational guidance, please refer to the product’s user manual.

2) Data formats

- On device/in transit: proprietary/binary radiometric JPG and IS5 files, AVI, JPG.
  - Radiometric JPG files are JPG format binaries with Fluke-defined internal organization. Certain metadata is in a proprietary format; visible light control image captures are JPG formats. Some data elements are not described in order to protect proprietary/trade secret practices, but export via the Related Service provides the processed temperature data.
- On export: using Related Service SmartView Classic PC software (free): CSV / JPG / PNG.
  - Schema/data dictionary: self-describing CSV.

3) Storage & retention

- On-device storage: Yes.
  - Storage capacity: 4,000–8,000 JPG files depending on included data captures.
  - User managed storage lifetime.
- Retention: on-device data retention is under user control (create, delete, transfer).
  - Configuration settings lifetime is controlled by the user, but settings are not exportable (factory reset available).
- Deletion/anonymization: not applicable – see Retention for measurement data; no usage data is collected by the connected device or the Related Service (SmartView).

4) User access, export & erase

- **Where:** SmartView Classic (**Software For Fluke Infrared Cameras**).

How – without software:

- All image data will be stored on the SD card (one SD card is included with camera purchase; others are available as standard products from standard retailers).
- Files are transferred from the SD card to a PC and thereafter controlled by the user.

How – using SmartView Classic:

- Export formats: CSV / JPG / PNG, plus also see the separate Related Service/software declaration (SmartView Classic) for additional capabilities.
- Limits/rate limits (if any): storage capacity and capture duration of the local PC.

Request erasure: customer-controlled PC.

5) Data Sharing with Third Parties

To the extent Fluke has access to the relevant data, you may authorize a third party to access such data by contacting Fluke using the details set out above, specifying the recipient and purpose of the data sharing. You may view and revoke authorized data transfers at any time via the same contact details.

Where data is stored locally on your device or within your own environment and is not accessible to Fluke, you are responsible for granting third-party access directly.

6) Terms of service, contract term & termination

As provided in the quote, order form, or agreement between you and Fluke. If you purchased the product through a distributor or reseller, the terms of service, contract term and termination are as agreed between you and that seller.

7) How Data Holder uses the data

If Fluke has access to any data generated through your use of a Fluke connected product or related service, this will be used in accordance with the applicable agreement between you and Fluke, through which you purchase Fluke’s products or services. The relevant Fluke entity details will be specified in the quote or order form as applicable.

Fluke may engage third parties to act as service providers and perform certain tasks on its behalf, such as processing or storing data generated in connection with your use of a Fluke

connected product or related service. For more information, please visit **https://www.fluke.com/en-us/fluke/privacy-policy**

8) Trade secrets

Proprietary/Trade Secret data is contained in the IS2- and IS3-format files. No trade secrets are contained in the export data formats (CSV, JPG, PNG).

No trade secrets are contained in the Related Service data.

9) Right to lodge a complaint

If you have a complaint relating to your Fluke connected product or related service, or the Data Act in general, you can contact Fluke using the details set out above. You also have the right to lodge a complaint with the relevant competent authority designated under Article 37 of the EU Data Act, in the Member State of your habitual residence, place of work or establishment.

Notice version: 1.0 **Last updated:** 2026-08-26